


MODEL NO. 4421-1C**Dimensions :****Features :**

Excellent lighting effect ,
perfect glare control ,
uniform and comfortable lighting
experience

**Luminaire**

Material	aluminum	Optics	Lens
Surface	WH		


Technical specification

Light source	COB	CCT	2700 /3000 /4000 /5000K
Beam angle	15° / 24° /36°	CRI	> 90
Luminous flux	300 lm		


Electrical specification

Total power	9W	Control dim	DALI /0-10V /Triac /wireless
Input voltage	220-240V 50/60Hz	Output voltage	28-42 V
Power factor	0.5	Output current	200mA


IP rating	IP 20	Recommended use	Indoor
Installation	RECESSED CEILING	Adjusted	swing 30° , rotate 355°
Storage Temperature	-20°Cup to max. 50°C	Packing	/

Light Distribution Curve

H (m)	D (m)	Em (lx)
1	0.3	4260
2	0.5	1065
3	0.8	473
4	1.1	266
5	1.3	170



H (m)	D (m)	Em (lx)
1	0.4	1950
2	0.9	488
3	1.3	217
4	1.7	122
5	2.1	78



H (m)	D (m)	Em (lx)
1	0.6	1380
2	1.3	345
3	1.9	153
4	2.6	86
5	3.2	55

Accessories