


MODEL NO. 4423-1C



Dimensions :



Features :

Excellent lighting effect ,
perfect glare control ,
uniform and comfortable lighting
experience



Luminaire

Material	aluminum	Optics	Lens
Surface	WH		

Technical specification


Light source	COB	CCT	2700 /3000 /4000 /5000K
Beam angle	15° / 24° /36°	CRI	> 90
Luminous flux	398 lm		

Electrical specification


Total power	12W	Control dim	DALI /0-10V /Triac /wireless
Input voltage	220-240V 50/60Hz	Output voltage	28-42 V
Power factor	0.5	Output current	300mA

IP rating	IP 20	Recommended use	Indoor
Installation	RECESSED CEILING	Adjusted	swing 30° , rotate 355°
Storage Temperature	-20°Cup to max. 50°C	Packing	/


Light Distribution Curve



H (m)	D (m)	Em (lx)
1	0.3	5492
2	0.5	1373
3	0.8	610
4	1.1	343
5	1.3	220



H (m)	D (m)	Em (lx)
1	0.4	4466
2	0.9	1117
3	1.3	496
4	1.7	279
5	2.1	179



H (m)	D (m)	Em (lx)
1	0.6	2102
2	1.3	526
3	1.9	234
4	2.6	131
5	3.2	84

Accessories